









LC Foam / LC Foam Hose Drop Station

MODEL: 915205

OVERVIEW

The LC Foam/LC Foam Hose Drop Station is a 2-way foam applicator for projecting 2 foaming chemicals on to any surface up close or at a distance. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrates into the water streams to create accurately diluted solutions using precision metering tips to control chemical usage. Rich, clinging foam is created by injecting compressed air into each foaming solution to greatly increase volume and coverage ability. Each foaming solution is then projected through a separate foam hose and fan nozzle at distances up to 12 feet.

Key Features

- Designed for foaming medium to large areas and objects
- Separate, color-coded hoses for incompatible chemicals
- Use 2 different chemicals or 2 different dilution ratios of the same chemical
- Projects a medium volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern foam nozzle for fast coverage (up to 12' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- Adjustable foam consistency (wet/dry)
- All stainless steel and polypropylene wetted components ensure years of trouble-free performance
- Industrial-strength design holds up in tough environments
- See other configurations of Lafferty city water pressure foamers in <u>Catalog 1</u>

Includes

- Stainless steel mounting bracket
- Machined polypropylene foamer body
- Stainless steel inlet and discharge ball valves
- 20 color-coded precision metering tips to set dilution ratios
- 1- 40' blue hose, polypropylene foam wand & fan nozzle
- 1- 40' red hose, polypropylene foam wand & fan nozzle



Options

Large Stainless Steel Hose Rack	# 224150
Stainless Steel Jug Racks	
Jug Rack, SS, 1 Gallon, Round/Square	# 224200
Jug Rack, SS, 2 1/2 Gallon	# 224210
Jug Rack, SS, 5 Gallon	# 224215
Lid & Suction Hose for 1 & 5 Gallon Pails Pail Lid Suction Hose Assembly	# 709101
Alternate Check Valves - EPDM Standard	
Check Valve, Chemical, PP/Viton, 1/4"	# 491315
Check Valve, Air, SS/Viton, 1/4"	# 491306

REQUIREMENTS

Chemical Concentrate

Water

 Temperature
 up to 160°F

 Pressure
 35 - 125 PSI

 Flow
 1.34 GPM @ 40 PSI

 Supply Line
 3/4"

 Compressed Air
 up to 3 CFM

Hose

Nozzle

Foam 50250 Foam 50250

APPLICATIONS

- Food & Beverage
- Animal Health
- Dairy
- Hatchery
- Industrial
- Janitorial/Sanitation
- Pharm/Bio
- Supermarkets
- And Many Other Applications!

Available from:



DEMA Australia 8/7-11 Parraweena Road Caringbah NSW 2229

Ph: +61 2 9525 5177 Fx: +61 2 9525 5033 Eml: sales@demaust.com