



Strip-It™ Sealer & Coating Stripper

DESCRIPTION

Aqua-Seal STC™ Strip-It™ is a safe, NO VOC (0 g/l) non-flammable, biodegradable, multi-purpose stripper. It formulated to stay wet for longer periods to give the product time to break down and help remove most sealers, epoxy grout haze, urethane coatings, synthetic finishes, adhesives, silicones and paints. Effectively dissolves heavy wax, and helps remove deep-set stains and heavy grease build-up.

USES

Use on all natural stone, grout, ceramic, porcelain, terracotta, Saltillo, quarry tiles, terrazzo, concrete, pavers and masonry surfaces.

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS

1. Do NOT spray;
2. Always Test first;
3. Read entire label and product technical bulletin before using;
4. Wear appropriate skin, eye and foot protection;
5. Use in a well ventilated area;
6. Floor will get slippery during stripping process. Take appropriate precautions to prevent slip falls;
7. Use when surface temperature is between 4°C and 32°C.

APPLICATION – STRIPPING:

1. Read entire label before using;
2. SHAKE WELL before using;
3. Sweep or vacuum surface;
4. Apply a liberal amount of Aqua-Seal STC™ Strip-It™ to a small manageable area of up to 4m²;
5. Do NOT dilute;
6. Spread with a roller, mop, sponge or brush;
7. Allow product to dwell minimum 1 hour without drying or until coating or residue softens. DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE;
8. Agitate with a solvent resistant scrub pads, scrub brush or scrub machine;
9. Remove the residue with a wet vac or with clean, absorbent white cotton towels;
10. Rinse thoroughly with clean water;
11. Repeat the process as necessary;
12. Surface ready for light traffic in minimum 1 hour or after all fumes have dissipated. Allow at least 48-hour drying time before applying Aqua-Seal STC™ sealers, coatings or floor finishes. Always test first.

COVERAGE

Approximately 10–40 square meters per 4 litres. The coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method, severity of the problem and dilution used.

LIMITATIONS

- Do not mix with other chemicals or allow product to come in contact with any non-recommended surfaces;
- Will affect the sealers, coatings, floor finishes and painted surfaces.

HANDLING AND STORAGE:

- Close container tightly after each use.
- Store in original container only.
- Store in temperatures between 4°C and 32°C.

FIRST AID

For advice, contact a Poisons Information Centre (Phone 131 126) or a doctor. If swallowed, do NOT induce vomiting. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information centre or a Doctor, or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin with and hair with running water. If irritation persists, seek medical attention. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of accident or if you feel unwell, seek medical advice immediately.

SAFETY DIRECTIONS

Avoid contact with skin and eyes. May cause stomach distress, nausea or vomiting. May cause respiratory tract irritation.

WARNING: KEEP OUT OF REACH OF CHILDREN

READ SAFETY DIRECTION BEFORE OPENING

WARRANTY

Aqua-Seal STC™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use.

ALWAYS DO A TEST FIRST.