OxiTreat HD™

Heavy Duty Acid Treatment

Problem Solvers

DESCRIPTION
Aqua-Seal STC™ OxiTreat HD™ is a fast acting concentrated acid treatment designed to remove most cement and grout haze, efflorescence, rust stains, mineral deposits, mortar residue and smears. OxiTreat HD™ will also remove most hard water stains, lime deposits, soap scum, and ground in dirt and grime. It will also etch concrete.

USES
Use on ACID RESISTANT natural stone, porcelain, ceramic and masonry surfaces.

TEST FIRST
The end user must determine the suitability of the product for their intended use. You should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results.

PRECAUTIONS
1. Always Test first;
2. Read entire label and product technical bulletin before using;
3. Wear appropriate skin and eye protection;
4. Concrete and grout to be cured as per the manufacturers spec;
5. Use when surface temperature is between 4°C and 32°C;
6. Do NOT use on acid sensitive/polished surfaces.

INSTRUCTIONS
1. Sweep, vacuum, or wipe surface;
2. Pre-wet the surface with clean water;
3. Dilute OxiTreat HD™ as follows:
   a) LIGHT: Mix 15 parts water to 1 part product;
   b) MODERATE: Mix 10 parts water to 1 part product;
   c) HEAVY: Mix 5 parts water to 1 part product;
4. Carefully apply the solution to wet surface with a sponge or mop;
5. Allow to dwell for no longer than 3-5 minutes – DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE;
6. Scrub with a white nylon pad, natural or nylon bristle brush – always work in small areas;
7. Flush thoroughly with clean water immediately after scrubbing;
8. Remove the dirty solution with a mop or a wet vac;
9. Rinse thoroughly with clean water as necessary;
10. Repeat the process as necessary always following the product instructions.

LIMITATIONS
- DO NOT USE ON ACID SENSITIVE/POLISHED SURFACES;
- Do not mix with other cleaners or allow product to come in contact with any non-recommended surfaces.
- Acids of all kinds may etch, lighten, or change the colour of cementitious material, metallic glazes and some natural stones such as marble and limestone.

COVERAGE
Approximately 50–270 square meters per 4 litres. The coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method, severity of the problem and dilution used.

HANDLING AND STORAGE:
- Close container tightly after each use. Store in original container only.
- Store in temperatures between 4°C and 32°C.

FIRST AID
For advice, contact a Poisons Information centre (Phone 131 126) or a doctor. If swallowed, do NOT induce vomiting. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information centre or a Doctor, or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention.

SAFETY DIRECTIONS
Wear eye protection when mixing or using.
Wear protective gloves when mixing or using.

POISON: KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTION BEFORE OPENING

CONTAINS
PHOSPHORIC ACID 240 G/L
UN No 1805
HAZCHEM 2 R
CLASS 8
PG III

TRANSPORTATION NAME
PHOSPHORIC ACID SOLUTION

WARRANTY
Aqua-Seal STC™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use.
ALWAYS DO A TEST FIRST.

Aqua-Seal STC Technical Support
Phone +61 2 9521 4000 or Email technical@aqua-seal.com.au
www.aqua-seal.com.au